



XsPoint

Highly reliable and secure
contactless card reader for
access control solutions

Part Number	XP-P1	XP-P2	XP-M1	XP-M2
Frequency	125KHz, ASK		13.56MHz, ISO/IEC 14443A	
Output Interface	Wiegand 26 Bits, Clock-and-Data		Wiegand 32 Bits	Wiegand 26-128 Bits
Aux. Output Interface		RS232 serial ASCII, 19200, N, 8, 1/ RS485 (Secure OSDP) Selectable		RS232 serial ASCII, 19200, N, 8, 1/ RS485 (Secure OSDP) Selectable
Read Range	Up to 7cm		Up to 5cm	
Support Tags	EM4100, TK4100, JH4101, EM4101		Mifare Classic 1K/4K, Ultralight, Desfire, Mifare Plus, Smart Card	
Visual Indication	Tri Color LED			
Green LED Control	Active low input to control the Green LED			
Red LED Control	Active low input to control the red LED			
Buzzer Control	Active low input to control the buzzer			
Tamper Output		Open Collector Active Low		Open Collector Active Low
Configuration	CSN Mode	CSN Mode	CSN Mode	CSN & Sector Read Mode, Configurable through master Card for Mifare 1K/4K
Color	Black			
Input Voltage	8-16V DC			
Input Current	66mA Max @12V DC		52mA Max @12V DC	
Housing	ABS-PC			
Protection	IP54	IP65	IP54	IP65
Operating Temp.	-10 to 55°C			
Weight	52 gram			
Dimension (mm)	H 100 x W 44.70 X D 16.70			
Warranty	Limited Lifetime			

Technical specifications may be changed from time to time without any prior notice due to continuous enhancements in the product.



Head Office

Spectra Technovision (India) Pvt. Ltd.
707-708-709, Venus Atlantis Corporate Park,
Prahlanagar, Ahmedabad-380015 India.

+91 79 44111222 ✉ sales@spectra-vision.com

Branch Offices

Mumbai ☎ +91 22 44111222
Bangalore ☎ +91 80 44111222

